


DESCRIPTION: TRIAD toroidal inductors are specifically designed to minimize transients. These devices store energy, and therefore, condition the output signal by leveling out the current waveform providing a more stable current supply. Generally used in high frequency circuits, our standardized design provides an economical solution for use in differential mode applications or as an output inductor.



TECHNICAL NOTES:

1. Nominal inductance values are typically 10% higher than minimum rating
2. Biased inductance measured at rated DC amps
3. Operation at rated current yields approximately 40 degrees C rise over 20 degrees C ambient



TOROIDAL INDUCTORS

TYPE NO.	MIN. Inductance (uH)		Rated DC AMPS	MAX DCR (mOhm)	Dimensions					Wt Lbs.
	NO BIAS	AT BIAS			A max	B max	C max	D	E	
FIT44-1	18.85	12.72	2.8	44.8	0.625	0.350	0.700	0.250	0.020	0.008
FIT44-2	14.75	9.82	3.4	30.7						
FIT44-3	12.30	7.75	4.0	23.4						
FIT44-4	8.06	5.22	4.8	15.9						
FIT50-1	47.40	29.00	2.8	78.9	0.700	0.475	0.750	0.300	0.020	0.012
FIT50-2	35.48	23.77	3.4	57.8						
FIT50-3	27.16	16.13	4.0	40.1						
FIT50-4	21.65	12.27	4.8	29.2						
FIT50-5	16.76	9.50	5.7	20.0						
FIT50-6	12.50	6.75	6.8	14.0						
FIT50-7	8.60	4.80	8.1	11.0						
FIT68-1	89.50	57.99	2.8	108.0	0.875	0.475	0.950	0.300	0.020	0.026
FIT68-2	71.10	41.59	3.4	86.1						
FIT68-3	54.81	33.05	4.0	59.9						
FIT68-4	43.30	26.63	4.8	42.4						
FIT68-5	33.15	18.79	5.7	28.8						
FIT68-6	24.31	13.56	6.8	20.2						
FIT68-7	18.64	10.23	8.1	14.8						
FIT80-1	128.00	74.04	4.0	95.2	0.975	0.625	1.100	0.450	0.026	0.045
FIT80-2	107.50	58.05	4.8	67.9						
FIT80-3	80.75	42.00	5.7	44.8						
FIT80-4	65.04	31.60	6.8	32.8						
FIT80-5	47.70	22.79	8.1	22.5						
FIT80-6	38.07	18.11	9.7	17.0						
FIT106-1	253.00	153.00	4.0	139.0	1.300	0.725	1.400	0.500	0.026	0.090
FIT106-2	197.00	113.00	4.8	106.0						
FIT106-3	154.00	84.00	5.7	74.0						
FIT106-4	116.00	61.90	6.8	48.5						
FIT106-5	93.00	48.00	8.1	39.1						
FIT106-6	70.05	35.30	9.7	24.0						

A FIT-KIT is available which includes one of each of the above listed components.