

# FP24-250

## Electrical Specifications (@25C)

1. Maximum Power: 6.0 VA
2. Primary Voltage:
  - Series: 230V @ 50/60 Hz
  - Parallel: 115V @ 50/60Hz
3. Secondary:
  - Series: 24.0VCT @ 0.250Amps
  - Parallel: 12.0V @ 0.500 Amps

## Description:

The FP24-250 is part of a series which has a long history of reliable service in the field, made from a proven design and constructed with UL recognized materials.

## Construction:

Wound on two dual channel nylon bobbin. Materials are UL recognized, Class B (130° C) rated.

## Safety:

These products are 100% tested for dielectric strength at 2KVAC, 60Hz between primary and secondary windings and between the primary / secondary windings and the core.

## Agency File:

UL: File E53148, UL 506, Class B General Purpose Transformer,  
 cUL: File E53148, UL 506, Class B General Purpose Transformer, Canadian Use



## Dimensions:


A	B	C	D	E	F	G	H
1.920	1.562	0.850	0.250	0.375	1.600	1.63	0.874

Units: In inches

Weight: 7.0 oz

Pin Dimension: .020 x .041 in

## Schematic:



**RoHS Compliance:** As of manufacturing date February 2016, all standard products meet the requirements of 2015/863/EU, known as the RoHS 3 initiative.

\*Upon printing, this document is considered "uncontrolled". Please contact Triad Magnetics website for the most current version. For soldering and washing information please see <http://www.triadmagnetics.com>

