

SPECIFIC TECHNICAL CRITERIA

UL 60950-1, First Edition Information technology equipment - Safety- Part 1: General Requirements	
Report Reference No	E204980-A14-UL-1
Compiled by	Davide Lin
Reviewed by	Kate Ou
Date of issue	2006-01-03
Standards	UL 60950-1:2003, First Edition CSA C22.2 No. 60950-1-03 1st Ed. April 1, 2003
Test procedure	Component Recognition
Non-standard test method	N/A
Test item description	Power Supply
Trademark	None
Model and/or type reference	AWSP100-5, AWSP100-12, AWSP100-24, EIPS100S05, EIPS100S12, EIPS100S24
Rating(s)	Input: 100-240Vac, 1.8A, 50-60Hz. Output: AWSP100-5 / EIPS100S05 : 5V / 20A AWSP100-12 / EIPS100S12 : 12V / 8.4A AWSP100-24 / EIPS100S24 : 24V / 4.2A

Particulars: test item vs. test requirements	
Equipment mobility	for building-in
Operating condition	continuous
Mains supply tolerance (%)	+10%, -10%
Tested for IT power systems	No
IT testing, phase-phase voltage (V)	N/A
Class of equipment	Class I (earthed)
Mass of equipment (kg)	0.63
Protection against ingress of water	IP X0

Possible test case verdicts:	
- test case does not apply to the test object	N / A
- test object does meet the requirement	Pass
- test object does not meet the requirement	Fail (acceptable only if a corresponding, less stringent national requirement is "Pass")

General remarks:

- "(see Enclosure #)" refers to additional information appended to the Test Report
- "(see appended table)" refers to a table appended to the Test Report
- Throughout the Test Report a point is used as the decimal separator

GENERAL PRODUCT INFORMATION:	
CA1.0	Report Summary
CA1.1	N/A
CB1.0	Product Description
CB1.1	Electronic Component mounted on the PWB and housed with metal Chassis.
CC1.0	Model Differences
CC1.1	<ul style="list-style-type: none"> - Model EIPS100S05 is identical to Model AWSP100-5, except for model designations. - Model EIPS100S12 is identical to Model AWSP100-12, except for model designations. - Model EIPS100S24 is identical to Model AWSP100-24, except for model designations. - Models AWSP100-24 and AWSP100-12 are similar to Model AWSP100-5 except for output rating, Transformer winding and Model designation.
CD1.0	Additional Information
CD1.1	N/A
CE1.0	Technical Considerations
CE1.2	The product was submitted and tested for use at the maximum ambient temperature (T _{ma}) permitted by the manufacturer's specification of: 35 degree C for Model AWSP100-5 and EIPS100S05 50 degree C for Model AWSP100-12, AWSP100-24, EIPS100S12 and EIPS100S24
CE1.4	The product is intended for use on the following power systems: TN
CE1.12	The following were investigated as part of the protective earthing/bonding: the pillar and the metal enclosure for protective bonding
CE1.14	The following are available from the Applicant upon request: Installation (Safety) Instructions / Manual
CF1.0	Engineering Conditions of Acceptability
CF1.1	For use only in or with complete equipment where the acceptability of the combination is determined by Underwriters Laboratories Inc. When installed in an end-product, consideration must be given to the following:
CF1.3	The end-product Electric Strength Test is to be based upon a maximum working voltage of: Model AWSP100-5:, Primary-SELV: 446 Vrms, 840 Vpk, Model AWSP100-12:, Primary-SELV: 463 Vrms, 820 Vpk, Model AWSP100-24:, Primary-SELV: 461 Vrms, 744 Vpk
CF1.5	The following secondary output circuits are SELV: All secondary outputs
CF1.7	The following secondary output circuits are at non-hazardous energy levels: All secondary outputs are not hazardous energy
CF1.10	The following output terminals were referenced to earth during performance testing: All outputs

CF1.11	The power supply terminals and/or connectors are: Suitable for factory wiring only, Not investigated for field wiring
CF1.12	The maximum investigated branch circuit rating is: 20 A
CF1.13	The investigated Pollution Degree is: 2
CF1.15	Proper bonding to the end-product main protective earthing termination is: Required
CF1.16	An investigation of the protective bonding terminals has: Been conducted
CF1.18	The following magnetic devices (e.g. transformers or inductor) are provided with an OBJY2 insulation system with the indicated rating greater than Class A (105°C): T1 (Class B)
CF1.19	The following end-product enclosures are required: Electrical, Fire
CF1.23	The equipment is suitable for direct connection to: AC mains supply
CF2.0	Terminal Block is not investigated for permanently connected
CF2.1	Enclosure opening shall be evaluated in End-Product