

WAU-Series (VI)

- II Efficiency Level: VI
- II Power Output: 12VA
- II Primary Rating: 120VAC 60Hz
- II Secondary Rating: 6VAC – 24VAC, 2000mA – 500mA
- II Temperature Rise: 30 Deg C Max at rated load
- II UL/cUL File: E341931, UL 1310
- II Dimensions (mm): Height: 79.6 Width: 59.7 Depth: 48.1




Electrical Specifications (@20C):



Triad P/N	Secondary Rating	Output Connection Type	Mounting Tab	Pass-Through Ground	Stock	Approvals
WAU060-2000	6VAC +/- 5% @ 2000mA	5.5x2.1x11mm barrel plug	No	No	Yes	cULus Approved
WAU060-2000-G	6VAC +/- 5% @ 2000mA	MOLEX 43030-0001	No	Yes	No	cULus Approved
WAU060-2000-S	6VAC +/- 5% @ 2000mA	2 Screw Terminal	No	No	No	cULus Approved
WAU060-2000-SG	6VAC +/- 5% @ 2000mA	3 Screw Terminal	No	Yes	Yes	cULus Approved
WAU060-2000T	6VAC +/- 5% @ 2000mA	5.5x2.1x11mm barrel plug	Yes	No	No	UL Approved
WAU060-2000T-G	6VAC +/- 5% @ 2000mA	MOLEX 43030-0001	Yes	Yes	No	UL Approved
WAU060-2000T-S	6VAC +/- 5% @ 2000mA	2 Screw Terminal	Yes	No	No	UL Approved
WAU060-2000T-SG	6VAC +/- 5% @ 2000mA	3 Screw Terminal	Yes	Yes	No	UL Approved
WAU090-1200	9VAC +/- 5% @ 1200mA	5.5x2.1x11mm barrel plug	No	No	Yes	cULus Approved
WAU090-1200-G	9VAC +/- 5% @ 1200mA	MOLEX 43030-0001	No	Yes	No	cULus Approved
WAU090-1200-S	9VAC +/- 5% @ 1200mA	2 Screw Terminal	No	No	No	cULus Approved
WAU090-1200-SG	9VAC +/- 5% @ 1200mA	3 Screw Terminal	No	Yes	Yes	cULus Approved
WAU090-1200T	9VAC +/- 5% @ 1200mA	5.5x2.1x11mm barrel plug	Yes	No	No	UL Approved
WAU090-1200T-G	9VAC +/- 5% @ 1200mA	MOLEX 43030-0001	Yes	Yes	No	UL Approved
WAU090-1200T-S	9VAC +/- 5% @ 1200mA	2 Screw Terminal	Yes	No	No	UL Approved
WAU090-1200T-SG	9VAC +/- 5% @ 1200mA	3 Screw Terminal	Yes	Yes	No	UL Approved
WAU120-1000	12VAC +/- 5% @ 1000mA	5.5x2.1x11mm barrel plug	No	No	Yes	cULus Approved
WAU120-1000-G	12VAC +/- 5% @ 1000mA	MOLEX 43030-0001	No	Yes	No	cULus Approved
WAU120-1000-S	12VAC +/- 5% @ 1000mA	2 Screw Terminal	No	No	No	cULus Approved
WAU120-1000-SG	12VAC +/- 5% @ 1000mA	3 Screw Terminal	No	Yes	Yes	cULus Approved
WAU120-1000T	12VAC +/- 5% @ 1000mA	5.5x2.1x11mm barrel plug	Yes	No	No	UL Approved
WAU120-1000T-G	12VAC +/- 5% @ 1000mA	MOLEX 43030-0001	Yes	Yes	No	UL Approved
WAU120-1000T-S	12VAC +/- 5% @ 1000mA	2 Screw Terminal	Yes	No	No	UL Approved
WAU120-1000T-SG	12VAC +/- 5% @ 1000mA	3 Screw Terminal	Yes	Yes	No	UL Approved

Triad P/N	Secondary Rating	Output Connection Type	Mounting Tab	Pass-Through Ground	Stock	Approvals
WAU160-750	16VAC +/- 5% @ 750mA	5.5x2.1x11mm barrel plug	No	No	Yes	cULus Approved
WAU160-750-G	16VAC +/- 5% @ 750mA	MOLEX 43030-0001	No	Yes	No	cULus Approved
WAU160-750-S	16VAC +/- 5% @ 750mA	2 Screw Terminal	No	No	No	cULus Approved
WAU160-750-SG	16VAC +/- 5% @ 750mA	3 Screw Terminal	No	Yes	Yes	cULus Approved
WAU160-750T	16VAC +/- 5% @ 750mA	5.5x2.1x11mm barrel plug	Yes	No	No	UL Approved
WAU160-750T-G	16VAC +/- 5% @ 750mA	MOLEX 43030-0001	Yes	Yes	No	UL Approved
WAU160-750T-S	16VAC +/- 5% @ 750mA	2 Screw Terminal	Yes	No	No	UL Approved
WAU160-750T-SG	16VAC +/- 5% @ 750mA	3 Screw Terminal	Yes	Yes	No	UL Approved
WAU200-600	20VAC +/- 5% @ 600mA	5.5x2.1x11mm barrel plug	No	No	Yes	cULus Approved
WAU200-600-G	20VAC +/- 5% @ 600mA	MOLEX 43030-0001	No	Yes	No	cULus Approved
WAU200-600-S	20VAC +/- 5% @ 600mA	2 Screw Terminal	No	No	No	cULus Approved
WAU200-600-SG	20VAC +/- 5% @ 600mA	3 Screw Terminal	No	Yes	Yes	cULus Approved
WAU200-600T	20VAC +/- 5% @ 600mA	5.5x2.1x11mm barrel plug	Yes	No	No	UL Approved
WAU200-600T-G	20VAC +/- 5% @ 600mA	MOLEX 43030-0001	Yes	Yes	No	UL Approved
WAU200-600T-S	20VAC +/- 5% @ 600mA	2 Screw Terminal	Yes	No	No	UL Approved
WAU200-600T-SG	20VAC +/- 5% @ 600mA	3 Screw Terminal	Yes	Yes	No	UL Approved
WAU240-500	24VAC +/- 5% @ 500mA	5.5x2.1x11mm barrel plug	No	No	Yes	cULus Approved
WAU240-500-G	24VAC +/- 5% @ 500mA	MOLEX 43030-0001	No	Yes	No	cULus Approved
WAU240-500-S	24VAC +/- 5% @ 500mA	2 Screw Terminal	No	No	No	cULus Approved
WAU240-500-SG	24VAC +/- 5% @ 500mA	3 Screw Terminal	No	Yes	Yes	cULus Approved
WAU240-500T	24VAC +/- 5% @ 500mA	5.5x2.1x11mm barrel plug	Yes	No	No	UL Approved
WAU240-500T-G	24VAC +/- 5% @ 500mA	MOLEX 43030-0001	Yes	Yes	No	UL Approved
WAU240-500T-S	24VAC +/- 5% @ 500mA	2 Screw Terminal	Yes	No	No	UL Approved
WAU240-500T-SG	24VAC +/- 5% @ 500mA	3 Screw Terminal	Yes	Yes	No	UL Approved

Output Connections types:



MOLEX CONNECTOR



SCREW TERMINALS



BARREL PLUG

RoHS Compliance: As of manufacturing date February 2016, all standard products meet the requirements of 2015/863/EU, known as the RoHS 3 initiative.

* Upon printing, this document is considered "uncontrolled". Please contact Triad Magnetics' website for the most current version.